CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Original survey record by J. Kimbrell, 1891 states: Set post 3 ft. long, 3" square, 12" in the ground, could not set deeper on account of rock underneath, for $\frac{1}{4}$ sec cor marked $\frac{1}{4}$ S on West face, from which:

A Pine 5" diam bears \$43\frac{1}{2}^0E 52 1ks dist marked $\frac{1}{4}$ S BT.

Index File No. C-5

DIAGRAM

TIN R38E

6

5

⅓

A Pine 20" diam bears $N6^{O}W$ 75 lks dist marked $\frac{1}{4}$ \$ BT. Raised mound of stone $1\frac{1}{2}$ ' high, 4' wide at base around post.

Description of corner evidence found: Found remains of the original mound of stone, 1 ft. high and 4 ft. diam., the corner post is gone, from which the remains of the original bearing trees:

A hole containing rotten wood, and a loose piece of wood bearing fragmentary scribe marks, size and species indeterminate, bears N9 0 W 49.8 ft., and an orig., 5" Pine now 14" Ponderosa Pine, in good condition, no marks visible bears S41 0 E 34.3 ft.

Description of monument and accessories I established to perpetuate the

original location of this corner: At the true corner point in this original mound of stone, we set a 2"x30" galvanized iron pipe, 12" in the ground to bedrock and rebuild this mound of stone, 4' diam and $1\frac{1}{2}$ ' high, with brass cap attached, marked:

From which new BT's:

A 10" Douglas Fir, scribed $^{11}\!\!\!/_{2}$ S6 BT" on a double blaze bears N1 $^{0}\!\!\!$ W 54.9 ft.,

An 18" Larch, scribed $^{1\!\!4}$ S5 BT" on a double blaze bears N51 ^{0}E 52.3 ft.

TIN R38E

\$6 + \$5 PLS 1099 1980

Attached brass washer, marked "LS 1099" to lower blaze of new BT's.

Placed steel fencepost approx. 5' North of monument with sign 54-4 attached.

Attached signs and painted BT's per <u>Standard Specifications</u> <u>For Cadastral Survey</u> U.S.F.S. Region 6, October 1979.

I hereby certify that the above described corner and/or accessories was established on July 6, 1980.

Compass Declination: 20° East

F

Witnesses: Tom Isaac

Tom Isaacson Loren Huntsman John Curtiss REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 22, 1977
GARY L. LANGLITZ
1699

Office of County Surveyor County of State of Oregon , I hereby certify that the within	Union	GARY L. LAN 1099
for record on the day of by	and the state of t	Ţ
orm R6-7100-57 (9/71)	: Raceived	☆ GPO—798-276
	Cate Filed	