


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

G-9

History of original corner establishment:

Original survey by contract dated Aug. 1891;
 The original notes read;
 Set a post for one quarter corner to Sec. 8 and 9
 from which;
 A fir 4" in diam bears S15°E 15 lks.; marked $\frac{1}{4}$ SBT;
 A tamarack 6" in diam bears N52°W 63 lks marked $\frac{1}{4}$ SBT;



Description of corner evidence found:


Fnd a fir snag 24" in diam at S15°E with scribe;
 Fnd a tamarack log down and decayed with full scribe at N52°W;

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	<u>52-84R</u>

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 2" pipe 30" in length 24" deep with a bronze cap on top.
 From the Position of the corner I set the following bearing trees;
 A 11" Grand Fir bears N35°W a dist of 25.7 lks scribed $\frac{1}{4}$ SBT;
 A 8" grand fir bears N37°E a dist of 9.2 lks scribed $\frac{1}{4}$ SBT;
 All distances are measured to BTscribe;
 I placed US Forest Service bearing tree signs on old and new bearing trees.

I stamped the disk.



Office of.....county..surveyor..... County of..... Union
 State of..... Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 1 day of Oct., 1973, at 1 o'clock P M. (signed)
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

