
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by Joseph G. Gray on a joint venture with O'Dell under GLO contract Number 120, dated May 27, 1867. Surveyor General record states:

Set 1/4 sec cor, deposited marked stone, and raised stone mound.



No record of subsequent monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found stone 12x10x4 inches marked 1/4, in a small mound of stone.

See Map of Survey No. 034-1994
DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

In place of the found stone, I set a $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 25 inches in the ground, from which;

NEW BEARING TREES:

A 11 inch diameter Ponderosa Pine bears N 7° E, 28.53 feet marked 1/4 S15 BT


A 20 inch diameter Double Bole Ponderosa Pine bears S 54° E, 19.80 feet marked 1/4 S22 on the left bole

A 21 inch diameter Ponderosa Pine bears S 68° W, 27.22 feet marked 1/4 X BT


A 8 inch diameter Ponderosa Pine bears N 61° W, 19.93 feet marked X BT

Buried stone north and alongside pipe.

Raised a mound of stone around monument, 3 foot base to top of cap. Painted a 6" red band around all BTs and attached Bearing Tree signs. Set a steel fence post approximately 3 feet East with Land Survey Monument sign attached.



I hereby certify that the above corner point was perpetuated as hereon described on June 21, 1994. Witnesses: Travis Foster and Pete Crabtree.



REGISTERED
PROFESSIONAL
LAT CURVEYOR

OREGON
JULY 10, 1964

DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.