


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

R-17

**History of original corner establishment:** Corner established in 1867 by Joseph G. Gray & William H. Odell under General Land Office contract no. 120.

Surveyor General Notes state;  
Set post corner for sections 22, 23, 26 & 27, deposited marked stone, and raised stone mound as per instructions. SUBSEQUENT SURVEY; C.T. Darley, county surveyor, May 30, 1913.

C.T. Darleys' survey states;  
The Northeast corner of section 27 located by large pile of stones and testimony of D.L. Sanderson.



**Description of corner evidence found:**


Found large mound of stones near the intersection of old fences. The distance from the northwest corner of section 27 agrees with Mr. Darleys' survey within 0.86ft.. No marked stone was found.

**Description of monument and accessories established to perpetuate the**

**original location of this corner** I set a 36"x1" iron pipe with a brass cap, 15" in the ground raised a large mound of stone for the corner to sections 22, 23, 26 & 27 From which new B.T.'S;

- A 14" lodgepole pine bears N 30 E 63.3ft. to the center of the tree, Scribed T1N R38E S23 BT.
- A 15" lodgepole pine bears S75-30E, 60.78ft. to the center of the tree. Scribed T1N R38E S26 BT.
- An 8" lodgepole pine bears S20W, 19.66 ft. to the center of the tree. Scribed T1N R38E S27 BT.
- A 14" lodgepole pine bears N31W, 13.8 ft. to the center of the tree. Scribed T1N R38E S22 BT.

I used a steel tape and a magnetic compass with declination 20 degrees East.



**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Gregory T. Blackman*

**OREGON  
JULY 13, 1973  
GREGORY T. BLACKMAN  
991**

Office of ..... County of .....  
State of ....., I hereby certify that the within instrument was filed in this county  
for record on the ..... day of .....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY  
SURVEYOR**

---

Date Received \_\_\_\_\_

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 76-84-R