


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-17

History of original corner establishment: Original corner established in 1867 by Joseph G. Gray and William H. Odell under General Land Office contract number 120. Surveyor General Notes State; Set post corner for sections 26, 27, 34 & 35 from which a pine 22" in diameter bears S5W 128 lks. a pine 14" in diameter bears S85E 5.9 lks. a pine 10" in diameter bears N25E 68 lks. a pine 12" in diameter bears N40W 77 lks.



SUBSEQUENT SURVEY; C.T. Darley, county surveyor, May 30, 1913.


C.T. Darleys' survey states;
The Southeast corner located by testimony of Jim and Bert Slack, old fence corners and bearing trees.

Description of corner evidence found:

I found a fence corner with the remains of an old fence to the North and to the East. No bearing trees were found. I accepted this position as the best available evidence, and on the basis of its harmonious fit with other deeds.

Description of monument and accessories I established to perpetuate the

original location of this corner Set 36"x1" iron pipe with brass cap, 30" in the ground for the corner to sections 26, 27, 34 & 35.
No bearing trees were taken.



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Gregory T. Blackman

**OREGON
JULY 13, 1972
GREGORY T. BLACKMAN
991**

Office of County of
State of , I hereby certify that the within instrument was filed in this office
for record on the day of
..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 85-84R