

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Land Surveying & Boundary Consulting


P.O. Box 19 Mill City, OR 97360 (503) 897-2722

## History of original corner establishment:

Not previously set.

## Description of corner evidence found:

Not previously set.



## Description of monument and accessories I established to perpetuate the original location of this corner:

Monument Set:

A 3 1/4 in. aluminum cap on a 5/8" x 30" rebar buried 29 ins. in the ground, bottom 26 ins. in concrete filled drill hole, magnet alongside, with rock collar.

Accessories Set:

A Douglas fir, 16 ins. diam., bears S 82 1/2° E 12.1 ft. marked N 1/16 S32 BT on a double blaze with brass washer marked PLS 2456.

A ponderosa pine, 29 ins. diam., bears S 80 1/2° W 67.7 ft., marked N 1/16 S31 BT on a double blaze with a brass washer marked PLS 2456.

Red paint, posts and signs added as needed.

NAD 83 (CORS 2002) Coordinates:

Geographic

State Plane (North Zone)

45°31'33.2876" N

N 209,394.488 Meters E 2,687,649.594 Meters

118°05'50.7786" W

Convergence 1° 42'14"

Equipment: Staff Compass, Var. 18° E, loggers tape,

clinometer

Date: September 2, 2003

Crew: Michael Cordoza, Collin Edwards-Hill

See also the Record of Survey filed concurrently with this certification.

REGISTERED PROFESSIONAL LAND SURVEYOR

> OREGON July 25, 1990 Evelyn R. Kalb 2456

EXPIRES: 06/30/2005

UNION COUNTY SURVEYOR

Date Received 12/8/03

Date Filed 12/31/03

Filed By K. Losinson Description

File Number <u>052-2003</u> R