CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by Timothy W. Davenport under GLO contract no. 102, dated July 20, 1863. Surveyor General record states:

Set qr sec post from which: A tamarack 18 in dia bears S25°E, 27 lks. A tamarack 6 in dia bears N50°W 20 lks.

No record of subsequent monumentation found in UNION COUNTY survey records.

T1N R39E A-07

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found no evidence of the original corner monument or its accessories.

Proportionate position falls in an old down North-South fence, approximately 15 feet North of an existing East-West fence.

See Survey Number 032-1997.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a $2\frac{1}{2}$ " x 30" aluminum pipe with $2\frac{1}{2}$ " aluminum cap marked as shown below, 26" in the ground, from which:

NEW BEARING TREES:

A 13" diameter Tamarack bears N 39°E, a distance of 43.93 feet, marked T2N R39E 1/4 S32 BT.

A 10" diameter Tamarack bears S 74°E, a distance of 12.25 feet, marked T1N R39E 1/4 S5 BT.

A 19" diameter Douglas Fir bears S 70°W, a distance of 16.22 feet, marked T1N R39E 1/4 S5 BT.

A 10" diameter White Fir bears N $17^{\circ}W$, a distance of 46.32 feet, marked T2N R39E 1/4 S32 BT.

Set a steel fence post approximately 2 feet South of the corner monument. I hereby certify that the corner was monumented on October 13, 1997. Witness: Greg Blackman Jr.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 17, 1988
RICK G. ROBINSON
2219

S 32

1/4

S 5

T 1 N

1997

OPLS 2219

UNION COUNTY SURVEYOR

Date Received 11-4-97

Renewal Date December 31, 1998

Date Filed 11-4-97

Filed By Stry of 7. Ble

I used magnetic compass and steel tape in the establishment of the accessories to this corner. The distance to the bearing trees is to a 50d spike driven on the right side of the tree at the root crown. I attached a brass washer marked OPLS 2219 to the BT blaze.