

UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:
NONE

No record of monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:
NONE

See Survey Number 025-1998

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by the survey I set a 2 1/2" x 30" aluminum pipe with cap 24 inches in the ground with a 1 foot mound of stone, marked as shown, from which:


NEW BEARING OBJECTS AND TREES:

A 17 inch Dia. Ponderosa Pine bears S 31° W, a distance of 41.00 feet, marked CE 1/16 BT

A 10 inch Dia. White Fir bears N 67° W, a distance of 26.95 feet, marked CE 1/16 BT

I hereby certify that the corner was monumented on August 5, 1998.
Witness: Greg Engelgau, and Norb Volny.

T 1 N R 39 E L-08



REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
July 17, 1986
RICK G. ROBINSON
2219

Renewal Date December 31, 1998



UNION COUNTY SURVEYOR

Date Received 8/10/98

Date Filed 8/29/98

Filed By Greg T. Clark

File Number 021-1998R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination. Distances are to a 60d spike driven into the root crown of the bearing tree in the right side. A brass washer marked OPLS 2219 was attached to the BT blaze.