
## UNION COUNTY SURVEYOR CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

ODOT DWG NO. 4B-26-11 states found marked rock Survey No. 17-80 set 5/8" iron pin from ODOT information DWG 4B-26-11

Survey No. 30-89 found monument set by Survey No. 17-80, calls out of position, sets new monument from ODOT information DWG 4B-26-11 Minor Partition No. 1994-001 found monuments set by Survey Nos. 17-80 and 30-89. Calls both out of position, uses new computed position based on ODOT information DWG 4B-26-11.



No record of subsequent monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found monuments set by Survey Nos. 17-80 and 30-89.

## DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At record bearing and distance from the found monuments of survey numbers 17-80 and 30-89, established by Minor Partition No. 1994-001, I set a 2½" brass cap on a 5/8"x30" copper clad iron pin, (Cap marked as shown below), 35" in the ground, from which:

A 5/8"x30" iron pin with 1 ½" aluminum cap, bears N53°E, a distance of 40.57 feet, marked UNION COUNTY SURVEYOR NE RP.

A 5/8"x30" iron pin with plastic cap, bears East, a distance of 20.00 feet, marked BGB SURVEY MARKER.

A 5/8"x30" iron pin with 1 ½" aluminum cap in North-South fence, bears S26°W, a distance of 36.54 feet, marked UNION COUNTY SURVEYOR SW RP.

a distance of 36.54 feet, marked UNION COUNTY SURVEYOR SW RP. A 5/8"x30" iron pin with 1 ½" aluminum cap in North-South fence, bears N38°W, a distance of 29.20 feet, marked UNION COUNTY SURVEYOR NW RP.


I hereby certify that the corner was monumented on April 8, 2001. Witnesses: Gregory T. Blackman Jr., Norbert W. Volny

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
July 17, 1986

RICK G. ROBINSON
2219

Renewal Date December 31, 2002



UNION COUNTY
SURVEYOR

Date Received 4/10/07

Date Filed 5/4/02

Filed By Agg 1.662

File Number \_\_

I used a Leica 530 GPS system with the Basis of Bearing being the same as Minor Partition No. 1994-001 in establishment of the new accessories. The distances are to the center of cap.