

**UNION COUNTY SURVEYOR**

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

None

No record of further monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

See Survey Number 025-1998

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

The position determined by the survey fell in a creek bed, therefore I set a 2 1/2" x 30" aluminum pipe with cap 5 feet south of the corner position as a witness corner marked as shown, 28 inches in the ground, from which:


NEW BEARING OBJECTS AND TREES:

A 17 inch Dia. Tamarack bears N 35° E, a distance of 26.19 feet, marked WC BT

A 15 inch Dia. White Fir bears S 54° w, a distance of 18.38 feet, marked WC X BT

I hereby certify that the corner was monumented on July 31, 1998.  
Witness: Jeff Madsen, Greg Engelgau, and Norb Volny.

T 1 N R 39 E M-08



REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Rick G. Robinson*

OREGON  
July 17, 1896  
RICK G. ROBINSON  
2219

Renewal Date December 31, 1990

BAGETT - GRIFFITH & BLACKMAN

T 1 N R 39 E

WC

SE 1/16 | S 17

1998

OPLS 2219

**UNION COUNTY  
SURVEYOR**

Date Received 8/10/98

Date Filed 8/29/98

Filed By *Greg T. Clark*

File Number 027-1998R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination. Distances are to a 60d spike driven into the root crown of the bearing tree in the right side. A brass washer marked OPLS 2219 was attached to the BT blaze.