


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHED:**

Corner originally established by Joseph G. Gray under GLO joint contract, with William H. Odell, No. 120, dated May 27, 1867. Surveyor General field notes state:

Set 1/4 section corner post deposited marked stone, and raised stone mound as per instructions.

T 1 N R 39 E X-09



**DESCRIPTION OF CORNER EVIDENCE FOUND:**

Found a 2' diameter mound of stone in East/West bearing fences. No marked stone found.

SEE SURVEY NUMBER 011-2018

**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

At the position of found stone mound, I set a 2 1/2" x 30" aluminum pipe with a 3" aluminum cap marked as shown, 25" in the ground, with mound of stone 3' base to top of cap.

From which:

**NEW BEARING OBJECTS:**

A 5/8" x 30" iron pin bears South 87°02' West, a distance of 20.42 feet, with 1 1/2" aluminum cap bears marked N RP.

A 5/8" x 30" iron pin bears South 86°19' East, a distance of 16.57 feet, with 1 1/2" aluminum cap marked E RP.

A Rock Outcrop bears South 16°10' West, a distance of 51.48 feet, marked X BO.

A 5/8" x 30" iron pin bears North 26°12' West, distance of 18.49, with 1 1/2" aluminum cap marked W RP.

A fence corner bears West approx. 9 feet from which fence bear East, West, and North.

I hereby certify that the corner was monumented on April 12, 2018.

Witness: Kyle A. Tucker

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**



OREGON  
June 2, 2010  
JEFFREY S. HSU  
83571

Renewal Date: June 30, 2019

BAGETT - GRIFFITH & BLACKMAN

T1N R39E

1/4

S32 | S33

2018

OPLS 83571

**UNION COUNTY  
SURVEYOR**

Date Received 4/25/18

Date Filed 4/25/18

Filed By [Signature]

File Number 010-2018

I used an RTK GPS in the establishment of the new accessories. Basis of Bearing is as per Survey 011-2018. Distances and bearings are to the center of the aluminum caps and the center of the X for the bearing object.