


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history.



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I located this East 1/16 Corner common to Sections 14, 23, T 1 N R 40 E, WM by survey. I then set a 2½ in. aluminum cap on a 30 in. pipe to within 4 in. above the surface of the ground. I then placed a mound of stone 3 feet dia. and 1 foot high around the monument. The cap being stamped as shown in the above diagram. I set two bearing trees as follows:

A Ponderosa pine 8 in. dia. bears N 86 53 E, 48.41 feet, scribed E-1/16S S 14 BT.
A larch 9 in. dia. bears S 18 50 E, 6.90 feet, scribed E-1/16S S 23 BT.

UNION COUNTY SURVEYOR	
Date Received	<u>11/23/92</u>
Date Filed	<u>12/18/92</u>
By	<u>[Signature]</u>
File No.	<u>095-1992 R</u>

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]
12-8-92

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Expires 12-31-93

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)