


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original notes state.
 Set Post for Secs. 13,14,23,24 from which;
 A larch 8" in diam bears N2°W 10 lks.
 A larch 10" in diam bears S85°W 20 lks.;
 A larch 10" in diam bears S40°E 20 lks.;
 A larch 12" in diam bears N45°E 40 lks.;



Description of corner evidence found:

A stump with BT. scribe was found at N2°W 10 lks dist.;

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	<u>95-84 R</u>

Description of monument and accessories established to perpetuate the original location of this corner

At the position of the corner I set a 2" pipe with brass cap on top at a depth of approx 2 ft. The pipe is 30" in length.;

From the position of the corner the following bearing trees were set;

A red fir 12" in diam bears N40°W at a dist. of 26.3 ft. scribed T1N, R40E, S14BT.;


A red fir 12" in diam bears S75°W at a dist. of 8.3ft. scribed T1N R40E S23BT.;

A red fir 10" in diam bears N26°E at a dist of 10.3 ft. scribed T1N R40ES13BT.;

A white fir 12" in diam bears S62°E at a dista of 19.6 ft scribed T1N R40ES24BT.;

All measurements were to the BT scribe.;

I stamped the disk



Office of Oregon county surveyor County of Union
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 27 day of Sept, 19 73, at 1 o'clock P.m. (Signed)
James G. Voelz by _____
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

OREGON
 MAY 4, 1956
 JAMES G. VOELZ
 381