


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by William H. Odell and Joseph G. Gray under glo joint contract number 120, dated May 27, 1867
Surveyor General record states:

Set 1/4 Sec cor post from which:

A fir 8 in dia bears S20°E 20 lks
A fir 22 in dia bears N85°W 19 lks



Description of corner evidence found:

NONE

Description of monument and accessories I established to perpetuate the

original location of this corner: At proportionate position, I set a 2 1/2 inch x 30 inch aluminum pipe with aluminum cap marked as shown, 30 inches in the ground from which:

New BTs

A 8 inch diameter tamarack bears S56°W 115.9 feet marked 1/4 S24 BT
A 14 inch diameter P.Pine bears N21°W 84.1 feet marked 1/4 S13 BT

Raised small mound of stone around monument
Corner set May 11, 1984
Witnesses: Duane Griffith and Rick Robinson

UNION COUNTY SURVEYOR

Date Received 5-29-84

Date Filed 5-31-84


By G. LANGLITZ, DEPUTY

File No. 862-84 R

REGISTERED PROFESSIONAL LAND SURVEYOR

Gregory T. Blackman

OREGON
JULY 13, 1973
GREGORY T. BLACKMAN
991



I used a steel tape and magnetic compass in the establishment of accessories. I used 18° East magnetic declination, and distances to the new BTs are to the center of the tree. I placed a brass washer marked OPLS 991 by the BT blaze of new BTs.

See survey number 21-84

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)