


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history.



Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner:

I located this NE-C-1/16 Corner, Section 23, T 1 N R 40 E WM by survey. I then set a 2½ in. aluminum cap on a 30 in. pipe to within 6 in. above the surface of the ground. I then placed a mound of stone 3 feet dia. and 1½ feet high around the monument. The cap being stamped as shown in the above diagram. I set two bearing trees as follows:
 A Ponderosa pine 12 in. dia. bears S 66 28 E, 15.51 feet, scribed 1/16S S 23 BT.
 A Ponderosa pine 8 in. dia. bears S 10 34 W, 71.93 feet, scribed 1/16S S 23 BT.

UNION COUNTY SURVEYOR
Date Received <u>11/23/92</u>
Date Filed <u>12/18/92</u>
By <u>Greg Blackman</u>
File No. <u>100-1992R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton
 12-8-92

OREGON JULY 10, 1964 JAMES H. HAMBLETON 645
--

Expires 12-31-93

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)