


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This $\frac{1}{4}$ Section Corner was set by deputy surveyor William H. Odell, under Contract No. 120, dated May 27, 1867. He states he set a basalt stone 3 in. x 10 in. x 18 in. for the $\frac{1}{4}$ Sec. Corner.



Description of corner evidence found:

At the assumed $\frac{1}{4}$ Sec. Corner location, I found an ancient fence corner with a small mound of stone around the corner post, all being located in an area where heavy farming activities have taken place for many years. Also an unmarked stone 2 in. x 9 in. x 17 in. was lying along side the corner post.

Description of monument and accessories I established to perpetuate the original location of this corner:

With no other evidence available I accepted the corner location as being the $\frac{1}{4}$ Sec. Corner, at which point I set a $2\frac{1}{2}$ in. brass cap on a 30 in. pipe to within 6 in. of the ground surface, with a mound of stone 3 feet dia. and $1\frac{1}{2}$ feet high around the pipe and cap. The cap being stamped as shown in the above diagram. With no trees available in the area, I then set four reference pins, being $\frac{5}{8}$ in. x 24 in. iron pins with a plastic cap stamped ORLS 645.

Reference pins are located as follows:

- Pin No. 1 bears North, 5 feet in plowed area.
- Pin No. 2 bears East, 5 feet in plowed area.
- Pin No. 3 bears South, 5 feet along fence line.
- Pin No. 4 bears West, 5 feet along fence line.

**UNION COUNTY
SURVEYOR**

Date Received 11/23/92

Date Filed 11/27/92

By *Huyon T. Black*

File No. 099-1992R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

11-23-92

OREGON
JULY 20, 1944
JAMES H. HAMBLETON
645

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)