

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: NONE

T1N R40E
C1/4 S23
LS2632
1995

Description of corner evidence: NONE

Description of monument and accessories set at corner location:

At the corner position I set a 2 1/2" x 30" aluminum pipe with attached 2 1/2" aluminum cap, set 20 inches in the ground, surrounded by a mound of stone. The cap is stamped as shown in the diagram.

From which I scribe new bearing trees:

- A 14" diam. Tamarack bears N62°E, 13.33 feet, marked C1/4S23BT.
- A 5" diam. P.Pine bears S50°E, 21.00 feet, marked XBT.
- A 6" diam. Fir bears S33°W, 51.24 feet, marked XBT.
- A 14" diam. P.Pine bears S67°W, 40.18 feet, marked C1/4S23BT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT's and magnetic compass, with 19° E. declination, with a washer stamped PLS 2632 nailed into the face. See Union County Survey No. 040-1995.

Witnesses: Jack Watson. Sept.5, 1995.

Office of County of
State of, I hereby certify that the within instrument was filed in this office
for record on the day of, 1995.
by

(COUNTY OFFICIAL)

**UNION COUNTY (DEPUTY)
SURVEYOR**

Date Received 9/30/95

Date Filed 10-27-95

By R. Robinson Deputy

File No. 028-1995R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Carl J. Stout
OREGON
JULY 20, 1993
CARL J. STOUT
#2732