


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:  
No previous history.



Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner:

I located the CE 1/16 Corner, Sections 23, T 1 N R 40 E WM by survey. I then set a 2½ in. aluminum cap on a 30 in. pipe to within 4 in. above the surface of the ground along side of a large boulder that is approximately 5 ft. x 4 ft. x 3 ft. high. Boulder is on SW side of the monument. No other stone is available to place around the monument. The cap being stamped as shown in the above diagram. I then set two bearing trees as follows:  
A Douglas fir 6 in. dia. bears S 81 00 E, 50.85 feet, scribed 1/16S S 23 BT.  
A Douglas fir 8 in. dia. bears S 58 00 W, 59.70 feet, scribed 1/16S S 23 BT.

**UNION COUNTY SURVEYOR**  
Date Received 11/23/92  
Date Filed 12/19/92  
By [Signature]  
File No. 101-1992 R

REGISTERED PROFESSIONAL LAND SURVEYOR  
[Signature]  
12-8-92  
OREGON JULY 10, 1964  
JAMES H. HAMBLETON  
645  
*Expires 12-31-93*

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)