


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history.



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I located the SE-C-1/16 Corner, Section 23, T 1 N R 40 E WM by survey. I then set a 2½ in. aluminum cap on a 30 in. pipe to within 6 in. above the surface of the ground. I then placed a mound of stone 3 ft. dia. and 1 foot high around the monument. The cap being stamped as shown in the above diagram. I then set two bearing trees as follows:
 A Ponderosa pine 8 in. dia. bears N 29 29 W, 51.07 feet, scribed 1/16S S 23 BT.
 A Ponderosa pine 9 in. dia. bears N 74 42 E, 28.90 feet, scribed 1/16S S 23 BT.

UNION COUNTY SURVEYOR
Date Received <u>11/23/92</u>
Date Filed <u>12/18/92</u>
By <u>[Signature]</u>
File No. <u>102-1992R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
<u>[Signature]</u>
<u>12-8-92</u>
OREGON JULY 10, 1964 JAMES H. HAMBLETON 645
<u>Expires 12-31-95</u>

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)