CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Odell and Gray in 1867 under GLO contract number 120, dated February 7, 1868.

Record states:

Set 1/4 sec cor. drove charred stake and raised stone mound as per instructions.

Subsequent survey:

None found

Township 1 North, Range 40 East R-15

27

T1N R40F S22 **S27** 2023 \$ 7855

Description of evidence found:

Description of monument and accessories established to perpetuate the location of this corner.

Corner positioned by single proportion as per survey 023-2023, set an aluminum pipe, 2 1/2 ins. diam., firmly set, flush with the ground, with 3 1/4 ins. aluminum cap mkd. as shown.

New Accessories:

An iron rod, 5/8 ins. diam. by 30 ins. long, with aluminum cap, 2 ins. diam. marked RM 1, bears N. 54° E., 8.9 ft. dist. An iron rod, 5/8 ins. diam. by 30 ins. long, with aluminum cap, 2 ins. diam. marked RM 2, bears S. 54° E., 10.1 ft. dist. An iron rod, 5/8 ins. diam. by 30 ins. long, with aluminum cap, 2 ins. diam. marked RM 3, bears S. 54° W., 8.1 ft. dist. An iron rod, 5/8 ins. diam. by 30 ins. long, with aluminum cap, 2 ins. diam. marked RM 4, bears N. 54° W., 10.2 ft. dist.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 8/29/2023.

Witnessed by: Matt Brockamp, LS Austin Brockamp

UNION COUNTY SURVEYOR Date Received File Number __05/-2023&

REGISTERED PROFESSIONAL AND SURVEYOR

OREGON MAY 20, 2015 MATTHEW R. BROCKAMP

78556 Registration expires 12/31/2023

