


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This Section Corner was set by deputy surveyor William H. Odell, under Contract No. 120, dated May 27, 1867. He states he set a post corner to Sections 22, 23, 26, 27 and drove a charred stake in a raised mound of stone as per instructions.



Description of corner evidence found:

At the assumed section corner location, I found no acceptable evidence of the original corner as farming activities in recent years has destroyed all evidence.

Description of monument and accessories I established to perpetuate the original location of this corner:

With no acceptable evidence of the original corner I used proportionate measurements to relocate the Section Corner. Then I set a 2½ in. aluminum cap on a 30 in. pipe within 6 in. above the ground surface, with a mound of stone 3 feet dia. and 1 foot high about the pipe and covering the cap. The cap being stamped as shown in the above diagram. With no trees available in the area, I then set four reference pins, being 5/8 in. x 24 in. iron pins with a plastic cap stamped ORLS 645. Reference pins are located as follows:

- Pin No. 1 bears North 10 feet.
- Pin No. 2 bears East 10 feet.
- Pin No. 3 bears South 10 feet.
- Pin No. 4 bears S 28 50 W, 99.95 feet and at the north-east corner of an old barn.

UNION COUNTY SURVEYOR
Date Received <u>11/23/92</u>
Date Filed <u>11/27/92</u>
By <u>[Signature]</u>
File No. <u>098-1992R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
<u>[Signature]</u>
<u>11-23-92</u>
JAMES H. HAMELTON 645

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)