## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

### History of original corner establishment:

Corner established by Odell and Gray in 1867 under GLO contract number 120, dated February 7, 1868.

#### Record states:

Set  $\frac{1}{2}$  sec cor. drove charred stake, dug pits, and raised stone mound as per instructions.

# Township 1 North, Range 40 East T-13

28

#### Subsequent survey:

None found



### Description of evidence found:

Found a stone mound.

# Description of monument and accessories established to perpetuate the location of this corner.

Set an aluminum pipe, 2 % ins. diam., firmly set, projecting 5 ins. above the ground with a 3 ft. diam. stone mound, with 3 % ins. aluminum cap mkd. as shown.

#### New Accessories:

A basalt stone, 2 ft. by 3 ft. by 3 ft., bears N 61° E., 38.5 ft. dist., marked XBO 1. A basalt stone, 2 ft. by 2 ft. by 3 ft., bears S 51° E., 23.3 ft. dist., marked XBO 2. A basalt stone, 1 ft. by 2 ft. by 1 ft., bears S 64° W., 68.3 ft. dist., marked XBO 3. A basalt stone, 1 ft. by 2 ft. by 1 ft., bears N 40° W., 144 ft. dist., marked XBO 4.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 8/29/2023.

Witnessed by: Matt Brockamp, LS Austin Brockamp

UNION COUNTY SURVEYOR

Date Received 9/18/23

Date Filed 9/18/23

Filed By

File Number 044-2628

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON MAY 20, 2015 MATTHEW R. BROCKAMP

Registration expires 12/31/2023

