CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Odell and Gray in 1867 under GLO contract number 120, dated February 7, 1868.

Set 1/4 sec cor. drove charred stake and raised stone mound as per instructions.

Subsequent survey:

Corner recovered in 1992 as per CS NO. 043-1992 by James H. Hambleton, PLS 645 as filed in the Union County Surveyor's office.

Record states:

Found mound of stone at an ancient four-way fence corner that fits very closely to what the original GLO notes call for. No evidence of the original post. Billy Hindman local long-time rancher had knowledge of this corner.

Township 1 North, Range 40 East T-17

27



Description of evidence found:

Found none

Description of monument and accessories established to perpetuate the location of this corner.

Corner positioned by single proportion as per survey 023-2023, set an aluminum pipe, 2 ½ ins. diam., firmly set, projecting out of the ground 5 ins. in a collar of stone, with 3 1/4 ins. aluminum cap mkd. as shown.

New Accessories:

A basalt stone, 1 ft. by 2 ft. by 2 ft., bears N., 54.7 ft. dist., marked XBO 1. A basalt stone, 1 ft. by 1 ft. by 1 ft., bears S 58° E., 200.3 ft. dist., marked XBO 2.

An iron rod, 5/8 ins. diam., by 30 ins. long, with aluminum cap, 2 ins. diam. marked RM 1, bears S. 34°W., 9.2 ft. dist.

An iron rod, 5/8 ins. diam., by 30 ins. long, with aluminum cap, 2 ins. diam. marked RM 2, bears N. 21°W., 7.4 ft. dist.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 8/29/2023.

Witnessed by: Matt Brockamp, LS Austin Brockamp

UNION COUNTY SURVEYOR Date Received File Number

REGISTERED **PROFESSIONAL** AND SURVEYOR

OREGON MATTHEW R. BROCKAMP 78556

Registration expires 12/31/2023

