
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT: None



No record of subsequent monumentation found in Union County survey records DESCRIPTION OF CORNER EVIDENCE FOUND:

See survey 017-1995

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: I set a 2½ x 30 aluminum pipe with aluminum cap marked as shown, 28 inches in the ground, with a mound of stone 3 feet at the base around the pipe, from

NEW BEARING TREES:

which;

A 10" Ponderosa Pine bears N73E, 35.82 feet, marked S 1/16 S25 BT. a 14" Ponderosa Pine bears S15W, 14.02 feet, marked S 1/16 S26 BT.

I hereby certify that the above corner point was perpetuated as hereon desdcribed on May 23, 1995. Witness: Jamie Petersen, Peter Crabtree


REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON

JEFFERY P. PETERSEN 2625

etner

Renewal Date: December, 31 1996



I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 2625 to the bearing tree blaze.

UNION COUNTY **SURVEYOR**

Date Received 6-1-95

Date Filed 6-/-95

File Number 007-1995 R

U-21