


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established by deputy surveyor William H. Odell, under GLO contract No. 120, dated May 27, 1867.

Surveyor General record states:

Set basalt stone, 12 x 16 x 18 in. for 1/4 Sec. cor.
On hillside facing East.




Description of corner evidence found:

In the area of the record position, I found a rock mound 5 ft. in dia. and 1 ft. high, with ancient moss covered stake planted firmly upright at center. A stone fitting record dimensions lay on surface of ground nearby. Could find no marks on stone. North-South existing wire fence is East 4 ft.

Description of monument and accessories I established to perpetuate original location of this corner:

At the center of the found rock mound:

Set a 3 1/4 in. dia. alum. cap on a 5/8 in. dia. by 30 in. long iron rod, buried 15 inches in the ground, re-built the mound of stone, 5 ft. dia. and 18 in. high, with t-post set southerly 2 ft., found stone fitting record placed into mound. Marked as shown:



From which:

A 5/8 in. dia. by 30 in. long iron rod with yellow plastic cap mkd: ELDER LS 51277 bears N 37° E, 13.1 ft. dist.

A 5/8 in. dia. by 30 in. long iron rod with yellow plastic cap mkd: ELDER LS 51277 bears S 24° E, 8.5 ft. dist.

A 5/8 in. dia. by 30 in. long iron rod with yellow plastic cap mkd: ELDER LS 51277 bears S 57° W, 15.6 ft. dist.

A chiseled X with chiseled BO above, in face of rock outcrop 6' by 3' by 2' high, marks are at northerly end of face, bears N 63° W, 6.6 ft. dist.

I hereby certify that the corner was monumented as described on Oct. 20, 2002 and accessories were taken with a hand compass set at 18 1/2° E. declination and steel tape.

Witness: Peter C. Elder

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 13, 1999
PETER C. ELDER
51277

Renewal Date: Dec. 31, 2003

**UNION COUNTY
SURVEYOR**

Date Received 12/2/02

Date Filed 12/31/02

By [Signature]

File No. 053-200212