CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by William H. Odell under joint contract with Joseph G. Gray under contract number 120, dated May 27, 1867.

Surveyor's record states: Drove charred stake and raised stone mound.

No record of subsequent monumentation found in UNION COUNTY survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

None

See Survey Number 023-1997.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by survey, I set a 2 1/2" x 30" aluminum pipe with 2 1/2" aluminum cap marked as shown below, 30" in the ground, with ring of stone.

BEARING TREES:

A 19" Ponderosa Pine bears S 81° E, 23.94 feet, marked 1/4 S36X BT.

A 15" Ponderosa Pine bears S 49° W, 9.86 feet, marked 1/4 S36 BT.

A 11" Ponderosa Pine bears N 33° W, 51.54 feet, marked 1/4 S25X BT.

A 16" Ponderosa Pine bears N 16° E, 79.12 feet, marked 1/4 S25 BT.

I hereby certify that the corner was monumented on July 18, 1997. Witnesses: Jeff Madsen and Greg Blackman Jr.


REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON JULY 20, 1993

JEFFERY P. PETERSEN 2625

eterser

Renewal Date: December 31, 1998



T1N R40E V-23

25

S

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 2625 to the bearing tree blaze.

UNION COUNTY SURVEYOR

Date Received 8-6-97

Date Filed 8-6-97

Filed By R. Rosenson, Domery

File Number 010-1997 R

V-23