CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Odell and Gray in 1867 under GLO contract number 120, dated February 7, 1868.

Record states: Set 1/4 sec. post corner, in steep hillside facing the South. From which a larch, 18 ins. dia., bears S. 81° W. 20 lks.

Township 1 North, Range 40 East X-9 **32**

Subsequent survey:

Corner recovered in 2002 as per CS NO. 045-2002 by Peter C. Elder, PLS 51277 as filed in the Union County Surveyor's office.

Found SW bearing tree, ancient stump with visible blaze and axe marks. Not remonumented this survey.



Description of evidence found:

Found the SW bearing tree, A 20 ins. diam. ancient larch stump, with visible axe marks.

Description of monument and accessories established to perpetuate the location of this corner.

Set an aluminum pipe, 2 ½ ins. diam., firmly set, flush with the ground in a collar of stone, with 3 ¼ ins. aluminum cap mkd. as shown.

New Accessories:

A Douglas fir, 17 ins. diam., bears N. 39° E., 6.4 ft. dist., scribed T 1 N R 40 E S 33 on single blaze.


A Douglas fir, 16 ins. diam., bears S. 44° E., 23.3 ft. dist., scribed T 1 N R 40 E S 33 on single blaze. A Douglas fir, 13 ins. diam., bears S. 85° W., 29.4 ft. dist., scribed XBT on single blaze.

A Douglas fir, 11 ins. diam., bears N 22° W., 18.8 ft. dist., scribed XBT on double blaze.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 8/29/2023.

Witnessed by: Matt Brockamp, LS Austin Brockamp



REGISTERED **PROFESSIONAL** AND SURVEYOR

OREGON MAY 20, 2015 MATTHEW R. BROCKAMP 78556

Registration expires 12/31/2023

