CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established

Township 1 North, Range 40 East X-12

33

Subsequent survey:

None found



Description of evidence found:

Description of monument and accessories established to perpetuate the location of this corner.

Corner positioned by survey 023-2023. Set an aluminum pipe, 2 ½ ins. diam., firmly set, projecting 5 ins. above the ground in a collar of stone, with 3 ¼ ins. aluminum cap mkd. as shown.

New Accessories:

A basalt stone, 1 ft. by 2 ft. by 1 ft., bears N. 45° E., 89.2 ft. dist., marked XBO 1.

A basalt stone, 1 ft. by 1 ft. by 1 ft., on top of a 4 ft. diam. stone mound, bears N. 55° W., 164.1 ft. dist., marked XBO 2.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 8/29/2023.

Witnessed by: Matt Brockamp, LS Austin Brockamp

UNION COUNTY SURVEYOR

Date Received 9/18/23

Date Filed 9/18/23

Filed By 052-2025

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
MAY 20, 2015
MATTHEW R. BROCKAMP

Registration expires 12/31/2023

