UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:


NONE

No record of subsequent monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

See Survey #028-1999
DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:
At position determined by survey, I set a 5/8" x 30" rebar with a 1 1/2" aluminum cap marked as shown below, 30" in the ground from which:



A 24" Ponderosa Pine bears N66°E, a distance of 136.38 feet, marked CS 1/16 S35 BT.

A 8" Douglas Fir bears $S26^{\circ}W$, a distance of 92.37 feet, marked CS 1/16 S35 BT.

I hereby certify that the corner was monumented on July 21, 1999. Witness: Norbert W. Volny, Gregory T. Blackman Jr.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON July 17, 1986

RICK G. ROBINSON 2219

Renewal Date December 31, 1998

S1/16 S35

C
1999

OPLS 2219

UNION COUNTY
SURVEYOR

Date Received 7/26/99

Date Filed 8///99

File Number <u>623-1999</u> R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 2219 to the bearing tree blaze.