

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-9

History of original corner establishment:


Corner established in 1863 by Timothy W. Davenport, Deputy Surveyor under Contract No. 102.

Surveyor General's records states:

Set post, cor. to secs. 32 and 33, near bank of last creek and about 400 lks. from the confluence of creeks below. From post

A 8" alder bears N 20 W, 10 lks.

A 40" pine bears N 42 E, 192 lks.



Description of corner evidence found:

At assumed corner location I found a 58" pine bears N 42 E, 190 lks. scribed T 1 N R 40 E S 33 BT. The face is open & not grown over. Found no other acceptable evidence.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap approx. 5" above surface of ground with a mound of stone around pipe that is 3 ft. dia. and 1 ft. high. Cap stamped as shown above.

New bearing tree:

A 4" P. pine bears N 14 W, 53.15 ft. scribed T 1 N R 40 E S 32 BT.

REGISTERED PROFESSIONAL LAND SURVEYOR

*James H. Hambleton*

OREGON  
JULY 10, 1964  
JAMES H. HAMBLETON  
645

Office of..... County of.....  
State of....., I hereby certify that the within Instrument was filed in this office  
for record on the ..... day of.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	96-84R