

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-19

History of original corner establishment:


Corner was established in 1863 by Timothy W. Davenport, Deputy Surveyor under Contract No. 102.

Surveyor General's records states:

Set $\frac{1}{4}$ sec. post; from which

A 36" pine bears S 20 W, 53 lks.

A 16" pine bears N 70 E, 58 lks.



Description of corner evidence found:

At assumed corner location I found a 19 x 7 x 6" basalt stone 10" above ground. No markings. Note: This stone apparently was set at some later date replacing the original wooden post. The stone was set in a mound of stone.

Found 16" pine stump with face charred bears N 70 E, 58 lks.

Found badly burnt pine stump approx. 36" dia. which bears S 20 W, 53 lks.

Description of monument and accessories established to perpetuate the original location of this corner

At corner location I set a 2" galv. iron pipe with brass cap approx. 18" above surface of rocky ground, in a mound of stone 3 ft. dia. and 1 1/2 ft. high. Cap stamped as shown above.

Bearing trees:

A 8" P. pine bears N 55 E, 45.75 ft. scribed $\frac{1}{4}$ S BT.

A 9" P. pine bears N 03 W, 67.20 ft. scribed $\frac{1}{4}$ S BT.

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton

OREGON
JULY 10, 1954
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of.....
..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 102-84 R