

*2002*

USDA-FOREST SERVICE GPO 940-117

Index File No. Z-2-25

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

Tract or Survey No. \_\_\_\_\_ Cor. No. \_\_\_\_\_


T 1N R. 41E

R.D. Union County Union

Merid. \_\_\_\_\_

N.F. W-W State OR

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

*None Found*

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

*20" PP stump*

PHOTO IDENTIFICATION DATA

Photo No. UBM-0 8-5-60

Filed At. 31B 23 Apr.

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

*Signature*

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

*Agency*

Signature

Title

Division

Headquarters

Date

7100-52 (3/68)

*10-9-63*

**UNION COUNTY SURVEYOR**

Date Found \_\_\_\_\_

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 28-87R

2-25

**UNION COUNTY  
CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner originally established by Timothy W. Davenport under GLO Contract Number 102, dated July 20, 1863. Surveyor General record states: Set post for cor. to secs. 31 & 36 Township 1 North Ranges 40 & 41 East from which:

A Red Fir 24 inch in dia bears N25°W 37 lks dist

A Pine 20 inch in dia bears N20°E 9 lks dist

A Pine 20 inch in dia bears S65°W 72 lks dist

Corner remonumented by Wayne L. Rogers, under BLM Group No. 350, Survey dated May 8-10, 1973. His record states:

The cor of Tps 1 N, Rs 40 and 41 E, determined at record bearing and distance from the remains of the original bearing trees: A

Pine snag, size indeterminate, bears N20°E, 9 lks dist, with fragmentary scribe marks visible on open blaze. A Pine snag, 24 ins diam, bears S65°W, 79 lks dist no marks visible on open burned blaze (Record 72 lks). A Fir root crown, bears N25°W, 37 lks dist, no marks visible. At the corner point set an iron post 28 ins long 2½ ins diam 24 ins in the ground with brass cap marked (see markings below) from which new bearing trees; A Fir, 10 ins diam bears N55°E, 55 lks dist mkd T1N R41E S31 BT. A Fir 14 ins diam bears N56°W, 126 lks dist mkd T1N R40E S36 BT.

No record of subsequent monumentation found in Union County survey records.

**Description of corner evidence found:**


Found 2½ inch diameter BLM brass cap marked as shown below.

**BLM Bearing Trees:**

Found a 12 inch diameter Douglas Fir N55°E, 55 lks live and vigorous with scribes visible.

Found a 16 inch diameter Douglas Fir N56°W, 126 lks live and vigorous with scribes visible.

Found the remains of the original GLO bearing trees as called in the BLM notes of Mr. Rogers.



See Union County Map of Survey Number 059 - 1991.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

NO ADDITIONAL REHABILITATION WAS DONE AT THIS CORNER

This monumentation sheet prepared to provide documentation of the existing corner monument and accessories.

I hereby certify that the above corner point was witnessed as hereon described on November 19, 1991.

Witnesses: Rick Robinson and Jeff Petersen

I used a steel tape and magnetic compass in the verification of the existing accessories. I used 20° East magnetic declination.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

Gregory I. Blackman

**OREGON**  
JULY 13, 1973  
GREGORY I. BLACKMAN  
991

**UNION COUNTY  
SURVEYOR**

---

Received 11/21/91

Witnessed 11/21/91

R. Robinson, Deputy

File No. 033-1991R