


Index
File No. J-5
T 1N R. 41E
Merid. will

CORNER RECORD (SEARCH)
(Ref. FSM 7151.4)

R.D. U7207 County _____
N.F. W-W State Ore

Tract or Survey No. _____
Cor. SW Cor No. Sec 8

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

none

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

*6' High stump scribing visible N35°W 84 IRs
Pine snag, down, rotted, blaze chopped out
no scribe visible Bears N 30°E 68 IRs.*

PHOTO IDENTIFICATION DATA

Photo No. _____
Filed At. _____
Object Ident. _____
Ident. By _____
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

PLANE COORDINATE POSITION DATA

State _____ Zone _____
X _____
Y _____
Estab. By _____
Agency

Signature
J.M.O. A.J.B.

Title _____ Division _____

Headquarters _____

Date
6/15/76

7100-52-(3.68)

UNION COUNTY SURVEYOR

Date Received _____

File # _____

File No. 27-87R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

4-5

History of original corner establishment:

Original corner set by Henry Meldrum under contract No. 450 dated June 11, 1882


Set basalt stone 14x11x5 inches with 4 notches on S and 5 notches on E edges, from which

A pine 8 inches diam bears S 10 E, 96 lks

A pine 10 ins diam bears N 3 E, 67 lks

A pine 30 ins diam bears N 35 W, 84 lks

No further recovery of this corner found in the County Surveyor's Record.



Description of corner evidence found:

Found NW BT snag standing with scribing visible

Found NE BT snag - down with scribing visible

Description of monument and accessories I established to perpetuate the original location of this corner:

With the aid of the Gov't Field Notes and remains of two BT's I intersect distances and establish corner point and set a 2x30 inch iron pipe with brass cap 24 inches in the ground with a mound of earth and stone to the top and marked the brass cap as shown in the diagram above, from which

A fir 15 ins diam bears N 53 E, 23.1 feet marked T1N R41E S8 BT

A fir 17 ins diam bears S 40 E, 57.6 feet marked T1N R41E S17 BT

A fir 15 ins diam bears S 4 W, 88.2 feet marked T1N R41E S18 BT

Posted 54-3 and 54-4 tags on all BT's.

Corner set for Boise Cascade Corp. by Verne H. Russell - County Surveyor

Date: April 13, 1983

Witness: Ray L. McVay

Used Silva Compass and steel tape to measure bearing and distance
Var. 20 E

| |
|------------------------------|
| UNION COUNTY SURVEYOR |
| Date Received <u>4-26-88</u> |
| Date Filed <u>4-27-88</u> |
| By <u>G. LANGRISH DEAN</u> |
| File No. <u>73-88 R</u> |

Office of..... County Surveyor..... County of..... Wallowa.....
State of..... Oregon..... I hereby certify that the within instrument was filed in this office
for record on the..... 6th..... day of..... May..... 19...83

..... by
(COUNTY OFFICIAL) (DEPUTY)