
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner not previously established.

T1N R41EZ-06



DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a Boise Cascade Location Tag South $54\,^{\circ}$ West approx. 8 ft.

SEE SURVEY NUMBER 056-2021

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At position by Survey I set a 5/8" x 30" iron pin, 25" in the ground, with 2 1/2" aluminum cap marked as shown below and in a collar of stone 3' diam., from which:

NEW BEARING OBJECTS:

A 7" Ponderosa Pine bears North 41° East a dist. of 28.10 ft., marked W 1/16 S32 BT. A 5" White Fir bears North 38° West a dist. of 16.00 ft., marked W 1/16 S32 BT.

Set steel fence post approx. 1 ft. North

I hereby certify that the corner was monumented on November 22, 2021.

Witness: Kyle A. Tucker

PROFESSIONAL
LAND SURVEYOR

OREGON
June 2, 2010

JEFFREY S. HSU
83571

Renewal Date: June 30, 2023

S32
W 1/16

S32

W 1/16

OPLS 83571
2021

UNION COUNTY
SURVEYOR

Date Received 12 9 7 1

Date Filed By Collins Defry

Filed By Charles Defry

File Number 063-2001 R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 14° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing trees. A brass washer marked OPLS 83571 is attached to the BT blaze of the new bearing trees.