


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-09

History of original corner establishment:

Original corner established in 1882 by H. Meldrum under contract #450
He set a post, 4'x5"x5", 24" in ground.
From which:
A 8" W. Larch bears N55°E, 14 lks.
A 7" W. Larch bears N17°W, 18 lks.
A 10" W. Larch bears S50°W, 21 lks.



Note: A. Gesener resurveyed this line in 1898 under contract #683. He stated that the original bearing, N17°W was actually N7°W

The blaze on the Orig NW BT in S32 more closely faces S17°E than S7°E. I used Henry Meldrum's bearing of S17°E, 18 lks. to establish the corner location.

Description of corner evidence found:

No corner monument found.

Orig. BT found:

A 14½" W. Larch bears N17°W, 18 lks., opened blaze, '41ES' visible. I counted 100+ growth rings from the blaze to present.

Description of monument and accessories I established to perpetuate the original location of this corner:

Cap is stamped:

From evidence, set 2½"x30" aluminum capped aluminum pipe rising 8", no stones available. Set steel fence post 3 ft. west of corner.

SC
T1N R41E
S32 | S33

RLS1848
1986

New BT's:

An 8½" Doug Fir bears N36½°E, 14.5 ft., blazed&scribed SCT1NR41ES33BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A ¾" brass disk stamped "LS1848 nailed to lower end of blazes. To find corner follow USFS posted boundary west up hill from the Minam River 2350 ft. to the corner.

Compass Declination: 19½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on Oct 30, 1986.



UNION COUNTY SURVEYOR

Date Received 11-21-86

Date Filed 11-26-86

By G. LANGLITZ, DEPUTY

File No. 262-86 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)