

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-13

History of original corner establishment:

Corner originally established by William H. Odell under GLO contract number 114, dated July 20, 1860. Surveyor General record states:

Set post corner for secs 33 and 34 from which:

A pine 10 in dia bears N17°E 80 lks

A pine 12 in dia bears N60°W 32 lks

A pine 20 in dia bears S15°W 43 lks

Corner was remonumented by Henry Meldrum under GLO contract number 450 dated June 11, 1882. Surveyor General record states: Set post for cor to secs 33 & 34 from which:

A pine 20 in dia bears N43°W 9 lks dist

A pine 18 in dia bears N16°E 29 lks dist


A fir 36 in dia bears S13°W 38 lks dist. Corner was remonumented by Alonzo Gesner under GLO contract number 683 dated June 7, 1898. Surveyor General record states: The cor to secs 33 & 34 which is a post. I reestablished as follows; Set a basalt stone 16x9x8 ins 12 ins in the ground. Accessories agreeing with the Surveyor General statement.

The corner was remonumented by the BLM by Wayne L. Rogers in 1973 (Group no. 350) His notes state: The cor of secs 33 and 34 determined at the record bearing and distance from the original bearing trees marked by Meldrum: A pine stump, size indeterminate, bears N16°E 29 lks dist no scribes visible, A fir stump size indeterminate, bears S13°W 38 lks


Description of corner evidence found:

Found a standard BLM brass cap monument marked as shown;

dist no scribes visible. A pine 32 in dia bears N13°W 9 lks dist with scribes visible. At the cor point set an iron post with brass cap marked; (cap markings shown below) from which a new bearing tree; A pine 12 ins diam bears N3 1/2°E 74 lks dist marked T1N R41E S34 BT.
No record subsequent monumentation found in Wallowa County survey records.



Found accessories as described by the BLM above.



See map of survey dated June, 1987.

Description of monument and accessories established to perpetuate the original location of this corner:

None

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Duane I. Griffith

OREGON
JULY 10, 1964
**DUANE I. GRIFFITH
644**

**UNION COUNTY
SURVEYOR**

Date Received 6-10-87

Date Filed 6-10-87

By G. LANGLITZ, DEPUTY

File No. 20-87 R

(See Survey 16-87)

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)

Re-monumentation of Certain Original Corner Points,
T. 1 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 31 and 32, on S. bdy., T. 1 N.,
R. 41 E., monumented with original basalt stone, 16 x 14
x 7 ins., firmly set 10 ins. in the ground, mkd. with 1
notch on W. and 5 notches on E. edges, from which the
remains of the bearing trees mkd. by Meldrum:

A sawed pine stump, 12 ins. diam.,
bears N. 54° E., 97 lks. dist., with
scribe marks T1N R41E S32 BL BT visible
on open double blaze.

A pine snag, 24 ins. diam., bears
S. $20\frac{1}{2}^{\circ}$ E., 105 lks. dist., with scribe
marks BL BT visible on open double blaze.

A pine, 24 ins. diam., bears N. 45° E.,
40 lks. dist., with scribe marks T1 B
visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 1 N R 41 E
S 31 | S 32
S 6
T 1 S R 41 E
1973

from which a new bearing tree

A fir, 12 ins. diam., bears N. 55° E.,
30 lks. dist., mkd. T1N R41E S32 BT.

Bury the corner stone alongside iron post.

The cor. of secs. 33 and 34, on S. bdy., T. 1 N.,
R. 41 E., determined at record bearing and distance,
from the remains of the bearing trees mkd. by Meldrum:

A decayed pine stump, size indeterminate,
bears N. 16° E., 29 lks. dist., no marks
visible.

A fir stump, size indeterminate, bears
S. 13° W., 38 lks. dist., no marks
visible.

A pine, 32 ins. diam., bears N. 43° W.,
9 lks. dist., with scribe mark B visible
on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 1 N R 41 E
S 33 | S 34
S 4
T 1 S
1973

from which a new bearing tree

A fir, 12 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ E.,
74 lks. dist., mkd. T1N R41E S34 BT.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 298-2013R