
## UNION COUNTY CERTIFIED RECORD OF LAND CORNER MONUMENIATION

History of original corner establishment:

For complete history see survey by Andrew Blachly for Oregon State Parks & recreation Department filed as Survey Number 026-1992 and filed in the office of the Union County Surveyor. Discourse is too long for this space allowed. This sheet is intended to describe the new accessories for the corner, and is transcribed by the Union County Surveyor for the Book of Bearing Trees.

Corner Not previously set.



Description of corner evidence found:

Nothing.

SEE SURVEY NUMBER 026-1992 FILED IN THE UNION COUNTY SURVEYORS OFFICE.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position determined by survey, I se brass cap on a 1½ " x 30 " Gal. Pipe in 3 ft. mound of stone 1 foot high. set a 2% Diameter

New Accessories:

An 8" diameter pine bears N 71° E 52.2 feet, scribed " X BT> with location poster. A 32" diameter Pine bears S 7° E 38.8 ft, scribed W 1/16 S36 BT with location poster.

I hereby certify that the above corner point was perpetuated as hereon described on March 4, 1992.

Billy J.W. Hermann, Harold Hanson. Witnesses: Blachly

Set By Andrew

R35E 8 25 OSP - LS 2168

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination.

UNION COUNTY SURVEYOR Data Received

V-22