
UNION COUNTY CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

For complete history see survey by Andrew Blachly for Oregon State Parks & recreation Department filed as Survey Number 026-1992 and filed in the office of the Union County Surveyor. Discourse is too long for this space allowed. This sheet is intended to describe the new accessories for the corner, and is transcribed by the Union County Surveyor for the Book of Bearing Trees.



Description of corner evidence found:

Found Pile of Stones.

SEE SURVEY NUMBER 026-1992 FILED IN THE UNION COUNTY SURVEYORS OFFICE.

Description of monument and accessories I established to perpetuate the original location of this corner:


At the Stone mound position, I set a $2\frac{1}{2}$ Diameter brass cap on a $1\frac{1}{2}$ " x 30 " Gal. Pipe from which:

New Accessories:
A 14" diameter Douglas Fir Bears N 55° W, 22.7 ' scribed X BT with metal location.
A 21" diameter Pine bears N 28° W, 12.0 ' scribed 1/4 S 36 BT with metal location poster.
A 29" diameter Douglas Fir bears N 2° E, 75.4' scribed X BT with metal location poster.
A 16" diameter Douglas Fir bears N 70° E, 23.4' scribed X BT with metal location poster.

Set blank carsonite post 4 ft. long 1.2 ' in ground. (Orange).

I hereby certify that the above corner point was perpetuated as hereon described on March 3, 1992.

Witnesses: Blachly Billy J.W. Hermann, Harold Hanson. Set By Andrew



I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination.

UNION COUNTY SURVEYOR Data Roceived File No. 052

Z-23