


C L I F I E D R E C O R D O F L A N D C O R N E R M O N U M E N T A T I O N

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:  
Corner not originally established.

T 1 S R 36 E Z-12



DESCRIPTION OF CORNER EVIDENCE FOUND:  
None.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by survey, I set a 5/8" x 30" rebar with 2 1/2" aluminum cap, marked as shown below, 29 inches in the ground, from which:

A 5 inch Ponderosa Pine bears South 81° West, a distance of 4.90 feet, marked E 1/16 S4 BT.

A 6 inch Ponderosa Pine bears North 26° West, a distance of 21.95 feet, marked E 1/16 S33 BT.

I hereby certify that the corner was monumented on November 7, 2012.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR



OREGON  
June 2, 2010  
JEFFERY S. HSU  
83571

Renewal Date: June 30, 2013

BAGETT - GRIFFITH & BLACKMAN

T1S R36E  
E 1/16  
S 33  
S 4  
T2S  
2012  
OPLS 83571

UNION COUNTY  
SURVEYOR

Date Received 11/12/12  
Date Filed 11/12/12  
Filed By R. Robinson Deputy  
File Number 076-2012R

I used a steel tape and magnetic compass in the establishment of new trees. I used 16° East magnetic declination. Distance is to a 60d spike in the right hand side of the trees. Bearing is to a brass washer marked OPLS 83571 in the lower BT blaze.