CHESEBRO & ALB

Land Surveying & Boundary Consulting

CERTIFIED RECORD OF LAND
CORNER MONUMENTATION

P.O. Box 19. Mill City, OR 97360 (503) 897-2722

C-8 CAP DIAGRAM C E 1/16 S 5 PLS 2456 2003

History of original corner establishment:

Corner not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Monument Set:

At the calculated position I set a standard U.S.F.S. monument (3 1/4 in. x 30 in. diam. aluminum cap on a 2 1/2 in. aluminum pipe), buried 26 ins. in the ground with a rock collar.

Accessories Set:

A white fir, 22 ins. diam., bears N 12 3/4° E 25.4 ft. marked CE 1/16 S5 BT on a double blaze with a brass washer marked PLS 2456.

A white fir, 36 in. diam., bears N 86 1/2° W 50.6 ft. marked CE 1/16 S5 BT on a double blaze with a brass washer marked PLS 2456.

Signs, red paint and nail side center on bearing trees.

NAD 83 (CORS 2002) Coordinates:

Geographic

State Plane (North Zone)

45°30'26.3600" N

N 207,366.979 Meters

118°04'52.6567" W

E 2,688,972.048 Meters

Convergence: 1°42'55"

Equipment: Staff compass, Var. 18° E, loggers tape,

clinometer

Date: Sept. 2, 2003

Crew: Ron Walter, Michael Cordoza, Collin Edwards-Hill

See also the Record of Survey filed concurrently with this certification.

REGISTERED PROFESSIONAL LAND SURVEYOR

> OREGON July 25, 1990 Evelyn R. Kalb 2456

Kall

EXPIRES: 06/30/2005

UNION COUNTY SURVEYOR

Date Received 12/8/03

Date Filed 12 31/03

Filed By R. ROBINSON DENTY

File Number <u>059-2003</u> R