

# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Land Surveying & Boundary Consulting

P.O. Box 19. Mill City, OR 97360 (503) 897-2722

## History of original corner establishment:

**David P. Thompson, Oct. 1, 1863,** Contract No. 103 Set post from which:

A larch 15 inch in dia. bears N 30° E 37 lks. (24.4 ft.) dist. A larch 15 inch in dia. bears N 30° W 33 lks. (21.8 ft.) dist.

### Description of corner evidence found:

Found no trace of the original monument or its accessories.

# C-9 CAP DIAGRAM T1S R38E 1/4 S 5 | S4 PLS 2456 2003

# Description of monument and accessories I established to perpetuate the original location of this corner:

Monument Set:

At the single proportionate position I set a standard U.S.F.S. monument (3 1/4 in. x 30 in. diam. aluminum cap on a 2 1/2 in. aluminum pipe), buried 24 ins. in the ground with a rock collar.

Accessories Set:

A Douglas fir, 16 ins. diam. bears N 15 1/2° E 27.0 ft. marked X BT on a double blaze. A white fir, 14 ins. diam., bears S 61 3/4° E 36.1 ft. marked 1/4 S4 BT on a double blaze.

A ponderosa pine, 24 ins. diam., bears S 48 1/4° W 142.4 ft. marked X BT on a double blaze.

A ponderosa pine, 15 ins. diam., bears N 28 1/4° W 48.5 ft. marked 1/4 S5 BT on a double blaze.

Signs, red paint and nail side center on bearing trees.

NAD 83 (CORS 2002) Coordinates:

Geographic

State Plane (North Zone)

45°30'26.6386" N

N 207,387.206 Meters E 2,689,359.789 Meters

118°04'34.7734" W Convergence 1°43'08"

Equipment: Nikon Total Station

Date: August, 2003

Crew: Ron Walter, Michael Cordoza, Collin Edwards-Hill

See also the Record of Survey filed concurrently with this certification.

REGISTERED PROFESSIONAL LAND SURVEYOR

> OREGON July 25, 1990 Evelyn R. Kalb 2456

all

EXPIRES: 06/30/2005

## UNION COUNTY SURVEYOR

Date Received 12/8/03

Date Filed 12 31 03

Filed By R. RUBINSON DRAWY

File Number Old -2003 R