


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

40.00 Set a basalt stone 14x10x5 ins. 9 ins in the ground for ¼ sec. cor., marked ¼ on W. face, from which:

A tamarack 10 ins. in diam. bears S 50° E, 18 lks dist. marked ¼S BT.

A tamarack 12 ins. in diam. bears S 40° W, 11 lks dist., marked ¼S BT.



Description of corner evidence found: None.

Set a 2½ x 30" aluminum pipe with 3" cap 22" in the ground with mound of stone, from which:

A 7" fir bears N 78° W, 33.0 feet scribed ¼S7 BT

A 9" fir bears N 31½° W, 32.5 feet scribed ¼S7 BT

A 7" fir bears S 41½° E, 26.2 feet scribed ¼S8 BT

A 14" fir bears S 13½° E, 17.4 feet scribed ¼S8 BT

Description of monument and accessories I established to perpetuate the original location of this corner:

UNION COUNTY SURVEYOR	
Date Received	<u>10/18/94</u>
Date Filed	<u>10/23/94</u>
By	<u>Gyng T. Black</u>
File No	<u>091-1994R</u>

REGISTERED	
PROFESSIONAL LAND SURVEYOR	
<i>Ronald E. Stoll 10/94</i>	
OREGON	
JULY 15 1983	
RONALD E. STOLL	
2058	

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

G-5