## Dependent Resurvey of the West Boundary, T. 1 S., R. 38 E., Willamette Meridian, Oregon

A tamarack, 22 ins. bears S. 18½° W., ft. dist., mkd 1/4 S13 BT.

Deposit a magn plastic case at the base of the stainles steel post.

Across broken W. slope.

Point for the cor. of secs. 7, 12, 13, and 18, at proportionate 5310.48 dist., there is no remaining evidence of the original cor.

> Set a stainless steel post, 28 ins. long, 2% ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

> > T 1 S R 37 E R 38 E S 12 | S 7 S 13 | S 18 2003

from which

- A spruce, 12 ins. diam., bears N. 56%° E., 26.9 ft. dist., mkd. T1S R38E S7 BT.
- A spruce, 25 ins. diam., bears S. 27° E., 61.2 ft. dist., mkd. T1S R38E S18 BT.
- A tamarack, 14 ins. diam., bears S. 73° W., 55.1 ft. dist., mkd. T1S R37E S13 BT.
- 18 A tamarack, N. 451/4° W., ins. diam., bears 62.7 ft. dist., mkd. T1S R37E S12 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located S. 30° W., 100 ft. dist. from a ravine, drains N. 50° W.

01' 38" E., bet. secs. 7 and 12

Over broken slope, thre fr, tamarack, and pine timber.

M sec. cor. of secs. 7 and R. 2655.24 at proportionate there is no remaining evidence of the original cor., not dist., the monumented

**UNION COUNTY SURVEYOR** Date Received

Date Filed

File No. \_