CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

80.00 Set a post 4 ft. long, 4 ins square, 24 ins in the ground for cor to Sec's 7, 8, 17 & 18 marked T1S8 on N.E., R38ES17 on S.E., S18 on S.W. and S7 on N.W. faces with 4 notchesin S. and 5 notches in E.edges, from which:

DIAGRAM
T 1 S R 38 E
S 7 | S 8
-----|----S 18 | S 17
LS 2058

A fir 14 ins in diam bears N.20° E. 41 lks dist, marked T1SR38EBT

A fir 20 ins in diam. bears S.60° E. 36 lks dist, marked T1SR38ES17BT A fir 20 ins in diam. bears S.45° W. 20 lks dist, marked T1SR38ES18BT A fir 12 ins in diam. bears N.30° W. 15 lks dist, marked T1SR38ES7BT

Description of corner evidence found:

A 29" fir bears S 52½° W, 11.8 feet A 24" snag bears N 13½° W, 10.4 feet A 27" fir bears N 20°20' E, 26.0 feet

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2½ x 30" aluminum pipe with 3" cap 22" in the ground with mound of stone, from which:

An 11" fir bears S 52¾° W, 11.8 feet scribed T1SR38ES18BT A 6" fir bears N 27½° W, 20.1 feet scribed T1SR38ES7BT A 7" fir bears S 70° E, 4.6 feet scribed T1SR38ES17BT

	The state of the s
certify that the within ins , 19 by	strument was filed in this office
County of	·
	2058
	OREGON JULY 19 1983 RONA AT STOLL
	1114 State 10/94
	LAND SURVEYOR
	PROFESSIONAL
	certify that the within in