


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

S 89°34' W on a true line bet Sec's 8 & 17
40.31 Set a basalt stone 16x9x8 ins, 11 ins in the ground for ¼ sec.
cor., marked ¼ on N. face and raised a mound of stone alongside.



Description of corner evidence found: None

Description of monument and accessories I established to perpetuate the original location of this corner: At a proportioned position I set a 2½x30" aluminum pipe with 3" cap 8" in the ground with mound of stone to cap, from which:

- An 8" fir bears S 26½° W, 39.3' scribed ¼S17 BT
- A 9" fir bears N 87° W, 30.7' scribed ¼S8 BT
- An 8" fir bears N 47° 45' W, 36.8' scribed ¼S8 BT
- A 12" fir bears N 83° E, 17.7' scribed ¼S8 BT

UNION COUNTY
SURVEYOR

Date Received 10/18/94

Date Filed 10/22/94

By [Signature]

File No. 095-1994R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature] 10/94

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)