

Dependent Resurvey of the West Boundary,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	
2655.24	<p>Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the original cor., not monumented.</p> <p>Descend over broken E. slope.</p>
5310.48	<p>Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist., there is no remaining evidence of the original cor., not monumented.</p> <hr/> <p>N. 0° 01' 38" E., bet. secs. 19 and 24.</p> <p>Descend over broken NE. slope, through fir, tamarack, and pine timber.</p>
2655.24	<p>Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate dist., there is no remaining evidence of the original cor., not monumented.</p> <p>Over broken slope.</p>
5310.48	<p>Point for the cor. of secs. 13, 18, 19, and 24, at proportionate dist., there is no remaining evidence of the original cor., not monumented.</p> <hr/> <p>N. 0° 01' 38" E., bet. secs. 13 and 18.</p> <p>Ascend over broken Southerly slope, through fir, tamarack, and pine timber.</p>
2655.24	<p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 37 E R 38 E 1/4 S 13 S 18 2003</p> <p>from which</p> <p style="text-align: center;">A tamarack, 30 ins. diam., bears N. 89° E., 9.3 ft. dist., mkd. 1/4 S18 BT.</p>

L-1

UNION COUNTY SURVEYOR	
Date Received	<u>6/12/11</u>
Date Filed	<u>6/23/11</u>
By	<u>R. ROBINSON, Deputy</u>
File No.	<u>026-2011R</u>

Dependent Resurvey of the West Boundary,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET											
	<p>A tamarack, 22 ins. diam., bears S. 18½° W., 23.3 ft. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Across broken W. slope.</p>										
5310.48	<p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 2½ ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 1 S</td></tr> <tr><td>R 37 E</td><td>R 38 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">2003</td></tr> </table> </div> <p>from which</p> <p>A spruce, 12 ins. diam., bears N. 56½° E., 26.9 ft. dist., mkd. T1S R38E S7 BT.</p> <p>A spruce, 25 ins. diam., bears S. 27° E., 61.2 ft. dist., mkd. T1S R38E S18 BT.</p> <p>A tamarack, 14 ins. diam., bears S. 73° W., 55.1 ft. dist., mkd. T1S R37E S13 BT.</p> <p>A tamarack, 18 ins. diam., bears N. 45¼° W., 62.7 ft. dist., mkd. T1S R37E S12 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located S. 30° W., 100 ft. dist. from a ravine, drains N. 50° W.</p> <hr/> <p>N. 0° 01' 38" E., bet. secs. 7 and 12.</p> <p>Over broken slope, through fir, tamarack, and pine timber.</p>	T 1 S		R 37 E	R 38 E	S 12	S 7	S 13	S 18	2003	
T 1 S											
R 37 E	R 38 E										
S 12	S 7										
S 13	S 18										
2003											
2655.74	<p>Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the original cor., not monumented</p>										

L-1

UNION COUNTY SURVEYOR	
Date Received	<u>6/12/11</u>
Date Filed	<u>6/23/11</u>
By	<u>R. Robinson, Deputy</u>
File No.	<u>026-2011R</u>