Dependent Resurvey of a Portion of the Subdivisional Lines, T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET

- A fir, 22 ins. diam., bears S. 14%° W., 118.0 ft dist., mkd. T1S R38E S30 BT.
- A fir, 17 ins. diam., bears N. 61%° W., 1492 ft. dist., mkd. T1S R38E S19 BT.

Deposit a magnet at the bottom of the drill hole.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 29 was searched for but not found.

From the dor. of secs. 19, 20, 29, and 30, the point for the cor. of sect. 19, 24, 25, and 30, on the W. bdy. of the Tp., bears S. 88 58' 40" W., 5132.1/ ft. dist., hereinbefore described.

N. 0° 07' 52" W., be secs. 20 and 21.

Over broken slope, through fir, tamarack, and pine timber with moderate undergrowth.  $\begin{tabular}{ll} \hline \end{tabular}$ 

2653.31

Point for the  $\frac{1}{4}$  sec/cor. of secs. 20 and 21, at proportionate dist., there is no remaining exidence of the original cor.

Set a stainless (teel post, 28 in), long, 2% ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T 1 S R 38 F 1/4 S 20 | S 21 2004

from hich

- A fir, 6 ins. diam., bears S. 74½° E., 24.° ft. dist., mkd. 1/4 S21 BT.
- A tamarack, 21 ins. diam., bears N. 7%° W., 7.3 f. dist., mkd. 1/4 S20 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Condition broken F glan

5306.62

Point for the cor. of secs. 16, 17, 20, and 21, at proportionate dist., there is no remaining evidence of the original cor.

N-9

UNION COUNTY SURVEYOR

Date Received 8/30/1/

Date Filed 8/30/1/

By R ROBINSON DEPOTY

File No. 037-2018

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.


T 1 S R 38 E S 17 | S 16 S 20 | S 21 2004

from which

- A fir, 17 ins. diam., bears N. 8%° E., 29.0 ft. dist., mkd. T1S R38E S16 BT.
- A fir, 18 ins. diam., bears S. 19%° E., 30.8 ft. dist., mkd. T1S R38E S21 BT.
- A fir, 8 ins. diam., bears S. 73%° W., 10.3 ft. dist., mkd. T1S R38E S20 BT.
- A fir, 20 ins. diam., bears N. 261/0 W., 43.0 ft. dist., mkd. T1S R38E S17 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, the cor. of secs. 15, 16, 21, and 22, Bears N. 89° 32' 23" E., 5245.05 ft. dist., perpetuated by Gregory T. Blackman, Registered Professional Land Su veyor No. 991, in 1990, recorded in the Union County survey records, survey file No. 43-90R, monumented with an aluminum post, 2½ ins. diam., firmly set, 7 ins. below the gravel surface of End Road, with aluminum cap mkd.



from which the remains of an original bearing tree

A sawed pine stump, 48 ins. diam., bears S. 80¼° E., 85.6 ft. dist., with axe marks visible (Record, S. 77° E., 83.8 ft.)

and accessories by Blackman

N-9

	UNION COUNTY SURVEYOR
Date	Received 8/30/(
Date	Filed 8/3///
Ву	R. ROBINSON SERVEY
File	No. 037-2011R