

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">UNION COUNTY SURVEYOR T 1 S R 38 E 21 22 —+— 28 27 1990 OPLS-991</p> <p>from which the remains of an original bearing tree</p> <p>The pitched over remains of a stump, size and species indeterminate, bears N. 30° E., 39.6 ft. dist., with axe marks visible. (Record pins)</p> <p>and bearing trees mkd. by Blackman</p> <p>A tamarack, 13 ins. diam., bears N. 4¼° E., 20.4 ft. dist., with healed double blazes.</p> <p>A fir, 29 ins. diam., bears S. 6° E., 3.4 ft. dist., with healed double blazes.</p> <p>A fir, 25 ins. diam., bears S. 52½° W., 53.0 ft. dist., with healed double blazes.</p> <p>A fir, 12 ins. diam., bears N. 62° W., 8.9 ft. dist., with healed double blazes.</p> <p>The ¼ sec. cor. of secs. 21 and 28 was searched for but not found.</p> <p>From this same point, the cor. of secs. 19, 20, 29, and 30, bears N. 89° 46' 05" W., 5282.09 ft. dist., determined at the center of a scattered mound of stone, 3 ft. diam., and is accepted as the best available evidence of the cor. position.</p> <p>Cement an aluminum rod, 22 ins. long, ¼ in. diam., 14 ins. in the ground, the bottom 8 ins. in a drill hole, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 1 S R 38 E S 19 S 20 —+— S 30 S 29 2003</p> <p>from which</p>
------	--

R-5

UNION COUNTY SURVEYOR	
Date Received	<u>6/12/11</u>
Date Filed	<u>6/23/11</u>
By	<u>R. ROBINSON DEPUTY</u>
File No.	<u>015-2011R</u>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	
	<p>A fir, 22 ins. diam., bears S. 14¼° W., 118.0 ft. dist., mkd. T1S R38E S30 BT.</p> <p>A fir, 17 ins. diam., bears N. 61½° W., 149.2 ft. dist., mkd. T1S R38E S19 BT.</p> <p>Deposit a magnet at the bottom of the drill hole.</p> <p>The ¼ sec. cor. of secs. 20 and 29 was searched for but not found.</p> <p>From the cor. of secs. 19, 20, 29, and 30, the point for the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., bears S. 88° 58' 40" W., 5132.16 ft. dist., hereinbefore described.</p>
	<p>N. 0° 07' 52" W., bet. secs. 20 and 21.</p> <p>Over broken slope, through fir, tamarack, and pine timber with moderate undergrowth.</p>
2653.31	<p>Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 38 E</p> <p>1/4</p> <p>S 20 S 21</p> <p>2004</p> </div> <p>from which</p> <p>A fir, 6 ins. diam., bears S. 74½° E., 24.2 ft. dist., mkd. 1/4 S21 BT.</p> <p>A tamarack, 21 ins. diam., bears N. 7¾° W., 7.3 ft. dist., mkd. 1/4 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue over broken E. slope.</p>
5306.62	<p>Point for the cor. of secs. 16, 17, 20, and 21, at proportionate dist., there is no remaining evidence of the original cor.</p>

R-5

UNION COUNTY SURVEYOR	
Date Received	6/12/11
Date Filed	6/23/11
By	R. ROBINSON DEARY
File No.	015-2011R