

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	<p>A fir, 17 ins. diam., bears S. 38½° E., 15.2 ft. dist., mkd. 1/4 S28 BT.</p> <p>A pine, 8 ins. diam., bears S. 87½° W., 19.9 ft. dist., mkd. 1/4 S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located E., 29 ft. dist. from an abandoned rock road, 12 ft. wide, extending N. 40° E. and S. 30° W.</p> <p>Continue over broken E. slope.</p> <p>5306.60 Point for the cor. of secs. 20, 21, 28, and 29, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin: 10px auto;"> <tr><td>T 1 S</td><td>R 38 E</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td colspan="2" style="text-align: center;">2003</td></tr> </table> <p>from which</p> <p>A tamarack, 17 ins. diam., bears N. 11½° E., 22.9 ft. dist., mkd. T1S R38E S21 BT.</p> <p>A fir, 6 ins. diam., bears S. 34½° E., 25.4 ft. dist., mkd. T1S R38E S28 BT.</p> <p>A fir, 4 ins. diam., bears S. 16½° W., 4.7 ft. dist., mkd. T1S R38E S29 BT.</p> <p>A fir, 18 ins. diam., bears N. 87½° W., 39.6 ft. dist., mkd. T1S R38E S20 BT.</p> <p>From this point, the cor. of secs. 21, 22, 27, and 28, bears N. 89° 39' 04" E., 5236.18 ft. dist., perpetuated by Gregory L. Blackman, Registered Professional Land Surveyor No. 991, in 1999, recorded in the Union County survey records, survey file No. 44-90R, monumented with an aluminum post, 2½ ins. diam., firmly set, flush with the ground, with aluminum cap mkd.</p>	T 1 S	R 38 E	S 20	S 21	S 29	S 28	2003	
T 1 S	R 38 E								
S 20	S 21								
S 29	S 28								
2003									

R-9

UNION COUNTY SURVEYOR	
Date Received	<u>6/12/11</u>
Date Filed	<u>6/23/11</u>
By	<u>R. ROBINSON, Deputy</u>
File No.	<u>017-2011R</u>