


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T-9

DIAGRAM



**History of original corner establishment:**

Corner originally established by David P. Thompson in 1863 under contract No. 103. Record states: Set post for 1/4 Sec. corner in mound of stone. In 2003 a dependant resurvey was made by BLM under special instructions dated April 29, 2003. \*\*BLM notes state: Point of 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the original cor. Set a stainless steel post 28 ins. long 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd. From which a fir 17 ins. diam., bears S38 1/4°E., 15.2 ft. dist., mkd. 1/4 S28 BT. A pine 8 ins. diam., bears S87 1/4°W., 19.9 ft. dist., mkd. 1/4 S29 BT. Deposited a magnet in white plastic case at the base of the stainless steel post.

**Description of corner evidence found:**

Found 2 1/2" o.d. stainless steel pipe with 3 1/4" brass cap set flush with ground in a 3 ft. dia. mound of stones. Cap marked as shown in diagram. A 17" dia. douglas fir with scribes visible on open single blaze bears S38 1/4°E - 15.2 ft. with 54-9 and BLM BT signs attached. A 9" dia. ponderosa pine with scribes visible on open single blaze bears S87 1/4°W - 19.9 ft. with 54-9 and BLM BT signs attached. There is a steel fence post with 54-2 sign 5 ft. south and a steel fence post with 54-9 and 54-2 signs 5 ft. north.

<p>REGISTERED PROFESSIONAL LAND SURVEYOR</p>
--

*William R. Wells*

<p>OREGON JULY 22, 1977 WILLIAM R. WELLS 1106</p>
---

*renews 6-30-06*

**Description of monument and accessories I established to perpetuate the original location of this corner:**

I add two new bearing trees.

A 8" ponderosa pine scribed 1/4 S28 BT on double blaze bears N53 1/2°E - 14.7 ft. Nailed 3/4" dia. brass washer stamped "PLS 1106" to face of blaze. Attached signs 54-3 and 54-9 to tree. Painted blaze and a 6" red band around tree.

A 11" ponderosa pine scribed 1/4 S29 BT on double blaze bears N20 1/2°W - 12.2 ft. Nailed 3/4" dia. brass washer stamped "PLS 1106" to face of blaze. Attached signs 54-3 and 54-9 to tree. Painted blaze and a 6" red band around tree.

Painted blaze and 6" red band around existing bearing trees.

This corner was maintained on Nov 3, 2004. Used magnetic compass with 18° East declination and measured to accessories with a steel tape. Measurements to bearing trees are to the center of tree.

Witnesses: Jason M. Wells LSIT.

\*\* The 2003 record by BLM is not yet recorded. We used preliminary copies of the field notes provided by the Wallowa Whitman National Forest.

Office of.....County of.....  
State of ....., I hereby certify that the within instrument was filed  
in this office for record on the .....day of ....., 20.....  
.....by.....  
(COUNTY OFFICIAL) (DEPUTY)

<p>UNION COUNTY SURVEYOR</p>	
Date Received	<u>12/9/04</u>
Date Filed	<u>12/10/04</u>
By	<u>R. ROBINSON, DEPUTY</u>
File No.	<u>084-2004R</u>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	<table border="1"> <tr><td>T 1 S</td><td>R 38 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2">2003</td></tr> </table>	T 1 S	R 38 E	S 30	S 29	S 31	S 32	2003	
T 1 S	R 38 E								
S 30	S 29								
S 31	S 32								
2003									
	<p>from which new bearing trees</p> <p>A tamarack, 17 ins. diam. bears N. 56½° E., 7.9 ft. dist., mkd. T1S R38E S29 BT.</p> <p>A tamarack, 14 ins. diam. bears S. 46° E., 18.5 ft. dist., mkd. T1S R38E S30 BT.</p> <p>A tamarack, 17 ins. diam., bears S. 21½° W., 19.7 ft. dist., mkd. T1S R38E S31 BT.</p> <p>A tamarack, 15 ins. diam., bears N. 61¼° W., 22.5 ft. dist., mkd. T1S R38E S30 BT.</p> <p>Deposit a magnet in a white plastic case at the base of and buried the mkd. stone alongside of the stainless steel post.</p> <p>Corner is located W., 35 ft. dist. from a dirt road, 12 ft. wide, extending N. 30° E. and S. 15° W.</p> <p>The ¼ sec. cor. of secs. 29 and 32 was searched for but not found.</p>								
	<p>N. 0° 05' 47" W., bet. secs. 28 and 29.</p> <p>Over broken E. slope, through fir, tamarack, and pine timber with moderate undergrowth.</p>								
2653.30	<p>Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p>								
	<table border="1"> <tr><td>T 1 S</td><td>R 38 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td colspan="2">2003</td></tr> </table>	T 1 S	R 38 E	1/4		S 29	S 28	2003	
T 1 S	R 38 E								
1/4									
S 29	S 28								
2003									
	<p>from which</p>								

T-9

UNION COUNTY SURVEYOR	
Date Received	6/12/11
Date Filed	6/23/11
By	R. ROBINSON, Deput
File No.	018-2011R

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	<p>A fir, 17 ins. diam., bears S. 38<math>\frac{1}{4}</math>° E., 15.2 ft. dist., mkd. 1/4 S28 BT.</p> <p>A pine, 8 ins. diam., bears S. 87<math>\frac{1}{4}</math>° W., 19.9 ft. dist., mkd. 1/4 S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located E., 29 ft. dist. from an abandoned rock road, 12 ft. wide, extending N. 40° E. and S. 30° W.</p> <p>Continue over broken E. slope.</p> <p>Point for the cor. of secs. 20, 21, 28, and 29, at proposed dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{2}</math> ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 38 E</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td colspan="2" style="text-align: center;">2003</td></tr> </table> <p>from which</p> <p>A tamarack, 17 ins. diam., bears N. 11<math>\frac{1}{4}</math>° E., 22.9 ft. dist., mkd. T1S R38E S21 BT.</p> <p>A fir, 6 ins. diam., bears S. 34<math>\frac{1}{4}</math>° E., 25.4 ft. dist., mkd. T1S R38E S28 BT.</p> <p>A fir, 4 ins. diam., bears S. 16<math>\frac{1}{4}</math>° W., 4.7 ft. dist., mkd. T1S R38E S29 BT.</p> <p>A fir, 18 ins. diam., bears N. 87<math>\frac{1}{4}</math>° W., 39.6 ft. dist., mkd. T1S R38E S20 BT.</p> <p>From this point, the cor. of secs. 21, 22, 27, and 28, bears N. 89° 39' 0" E., 5236.18 ft. dist., perpetuated by Gregory T. Blackman, Registered Professional Land Surveyor No. 991, in 1990, recorded in the Union County survey records, survey file No. 44-90R, monumented with an aluminum post, 2<math>\frac{1}{2}</math> ins. diam., firmly set, flush with the ground, with aluminum cap mkd.</p>	T 1 S	R 38 E	S 20	S 21	S 29	S 28	2003	
T 1 S	R 38 E								
S 20	S 21								
S 29	S 28								
2003									

T-9

UNION COUNTY SURVEYOR	
Date Received	6/12/11
Date Filed	6/23/11
By	R. ROBINSON DEARY
File No.	018-2011R